



# 630 & 1250 Mailbox Material Specification Sheet

MIDDLE VERTICAL BAR:	EXTRUDED 6063-T6 ALUMINUM, MILL FINISH 0.44 X 0.72 CROSS SECTION
OUTER VERTICAL BAR:	EXTRUDED 6063-T6 ALUMINUM, MILL FINISH 0.72 X 0.25 CROSS SECTION
TOP BAR:	EXTRUDED 6061-T6 ALUMINUM, ANODIZED FINISH 0.84 X 0.68 CROSS SECTION
BOTTOM BAR:	EXTRUDED 6061-T6 ALUMINUM, ANODIZED FINISH 0.84 X 0.19 CROSS SECTION
BACK, BOTTOM & SIDE PANELS:	GALVANNEALED STEEL 24 GAUGE THICKNESS
SINGLE COMPARTMENT DOOR:	EXTRUDED 6063-T5 ALUMINUM, ANODIZED FINISH 0.08 NOMINAL THICKNESS 0.25 RIB THICKNESS
DOUBLE COMPARTMENT DOOR:	EXTRUDED 6063-T5 ALUMINUM, ANODIZED FINISH 0.13 NOMINAL THICKNESS 0.25 RIB THICKNESS
OUTER TRIM:	EXTRUDED 6063-T5 ALUMINUM, ANODIZED FINISH 1.13 X 1.13 CROSS SECTION

**NOTES:**

1. MATERIAL SPECIFICATIONS SHOWN ARE APPROVED BY U.S. POSTAL SERVICE FOR REPLACEMENT PURPOSE ONLY.
2. ALL DIMENSIONS ARE IN INCHES.

PRODUCT SERIES: 630 & 1250 SERIES MAILBOX			
MATERIAL SPECIFICATION SHEET			
 <p>5935 Corporate Drive • Manhattan, KS 66503 www.auth-florence.com • (800) 275-1747 A GIBRALTAR INDUSTRIES COMPANY </p>	MODEL VERTICALS	REV A	
	SCALE NONE	LAST REV DATE 11/17/08	
	DRAWING NUMBER CS2037	DRAWN BY NBC	SHEET 1 OF 1